

**CLAIMS**

5

1. A method for combining at least two adjacent image segments to form a larger composite image comprising:

establishing a first region in which a first image segment will be printed;

10

establishing a second region in which a second image segment will be printed;

defining a buffer region associated with both image segments;

15

printing the first image segment and the buffer region;  
modifying the intensity in the buffer region by a first ramp value;

printing the second image segment and the buffer region; and

20

modifying the intensity in the buffer region by a second ramp value.

2. A method according to claim 1 wherein the image segments are substantially overlapping in the buffer region.

25

3. A method according to claim 1 wherein the first ramp rate and the second ramp rate are opposite one another.

4. A method according to claim 1 wherein the intensity in the buffer region sums to substantially full scale.

30

5. A method according to claim 1 wherein the buffer region is represented by a number of pixels from the first image segment and a number of pixels from the second image segment.

35

09882138-061501

1 45223/TJD/O125

6. A method according to claim 1 wherein the printing is done through use of a photosensitive medium and intensity in the buffer region is modified by modulating the amplitude of a beam of electromagnetic radiation capable of exposing a photosensitive medium.

7. A method according to claim 6 wherein the intensity in the buffer region is modified by modulating the amplitude of a beam of light.

8. A method according to claim 6 wherein the intensity in the buffer region is modified by modulating the amplitude of a laser beam.

9. A method according to claim 6 wherein the amplitude of the beam is modified by external modulation.

10. A method according to claim 6 wherein the amplitude of the beam is modified by internal modulation.

11. A method according to claim 6 wherein the amplitude of the beam is modified by acoustic modulation.

12. A method according to claim 11 wherein the amplitude of the beam is modified by an Acousto-Optic Modulator.

13. A method according to claim 1 wherein the printing of the first and second image segments is achieved through a process selected from the group consisting of scanning a photosensitive medium by a rotating polygon, rotating single facet mirror or rotating holographic scanner illuminated by the exposing radiation source.

35

1 45223/TJD/O125

14. A method according to claim 1 wherein the printing of  
the first and second image segments is achieved through having  
5 a photosensitive medium exposed by a fixed pattern array of  
individually segmented light sources.

15. A method according to claim 14 wherein the printing of  
the first and second image segments uses a laser beam.

10

16. A method according to claim 14 wherein the printing  
of the first and second image segments uses light valves  
illuminated by a light source.

15

17. A method according to claim 14 wherein the printing  
of the first and second image segments uses micro-mirrors  
illuminated by a light source.

20

18. A method according to claim 1 wherein the printing of  
the first and second image segments is achieved through having  
a photosensitive medium exposed by a fixed pattern array of  
radiation sources.

25

19. A method for creating a buffer region for a composite  
image comprising:

defining the region as a number of pixels extending  
into any two adjacent image segments;

30

defining a first rate at which the intensity of the  
pixels in the buffer region will be attenuated across the  
region in printing a first image segment; and

defining a second rate at which the intensity of the  
pixels in the buffer region will be attenuated across the  
region in printing a second image segment.

35

1 45223/TJD/O125

20. A method according to claim 19 wherein the first rate  
and the second rate at which the intensity of the pixels is  
5 attenuated are opposite one another.

21. A method according to claim 19 wherein the intensity of  
the pixels in the buffer region sum to substantially full scale.

10 22. A printing system comprising:  
a pixel counter;  
an integrator which outputs an intensity value from an  
input ramp rate and an initial value;  
a multiplier which converts digital pixel data and an  
15 intensity value into analog data; and an intensity  
modulator.

23. A printing system according to claim 22 wherein the  
intensity modulator is an amplitude modulator.

20 24. A printing system according to claim 23 wherein the  
amplitude modulator is an Acousto-Optic Modulator (AOM).

25 25. A printing system according to claim 22 wherein the  
intensity modulator is a phase modulator.

26. A printing system according to claim 22 wherein the  
intensity modulator is a frequency modulator.

30 27. A printing system according to claim 22 wherein the  
intensity modulator is a code domain modulator.

35

1 45223/TJD/O125

28. A printing system comprising:

means for counting pixels;

5 means for computing an intensity value from a ramp rate  
and an initial value;

means for converting an intensity value and digital  
pixel data into analog data;

and means for modulating intensity.

10

29. A printing system according to claim 28 wherein the  
ramp rate is defined as the percentage of modulation per in-scan  
pixel.

15

30. A printing system according to claim 28 wherein the  
intensity value is computed from a ramp rate and an initial value  
by an integrator.

20

31. A printing system according to claim 28 wherein the  
intensity value and digital pixel data are converted into analog  
data by a multiplier.

25

32. A printing system according to claim 28 wherein a means  
for modulating intensity is amplitude modulation.

33. A printing system according to claim 32 wherein the  
amplitude modulation is accomplished by an Acousto-Optic  
Modulator.

30

34. A printing system according to claim 28 wherein the  
means for modulating intensity is phase modulation.

35. A printing system according to claim 28 wherein the  
means for modulating intensity is frequency modulation.

35

1 45223/TJD/O125

36. A printing system according to claim 28 wherein the means for modulating intensity is code domain modulation.

5

10

15

20

25

30

35

09882138-061501  
105190-88128860